

5721-23

Industrial 90/95 W PoE Splitter



Description

The FASTCABLING 5721-23 95W PoE splitter is designed for pair working with FASTCABLING 95W PoE injector, together to deliver 72W (12VDC 6A) power budget. Dual PD signature architecture is implemented to guarantee safety power transport between the injector and splitter. The rugged design of this product combined with best industrial-grade components to offer high reliability and long-term performance.

Typical Application

- Retail
- Convenience Store
- Workshop
- Logistics
- Home
- and others

5721-23	
Dimensions	120 *100 *35 mm
Weight	442g
Networking Interfaces	(1) 10/100/1000 Mbps PoE Ports (1) 10/100/1000 Mbps Ethernet Ports
PoE Interfaces	IEEE802.3af/at/bt
PSE Power on RJ-45	Data Pairs 1/2(+),3/6(-) Spare Pairs 4/5(-),7/8(+)
Power Method	Power over Ethernet
Max. Power Output	DC12V, 6A
PoE budget	72W
LEDs Per Port	V1(Green), PoE(Orange)
ESD/EMP Protection	Air: ± 8 kV, Contact: ± 6 kV
Surge Protection	Different mode ± 4 kv, Common mode ± 6 kv
Operating Temperature	-40°C ~ 75 °C
Operating Humidity	5% ~ 90% non-condensing
Certifications	CE, FCC, IC
Input Voltage Range	38-55V DC