

5538-65

4 Port Industrial Hardened PoE Switch



Description

The Fastcabling Industrial Hardened PoE Switch is designed for long-distance stable power and data transmission, especially for the deployment in the hardest environments. It is utilized hardened grade components with a wide range operating temperature from -40 °C to 75 °C to satisfy harsh environments installation. The switch complies with IEEE 802.3at PoE+ standard to supply high powered ip devices.

Typical Application

- Retail
- Convenience Store
- Workshop
- Logistics
- Home
- and others

5541-56	
Dimensions	177×155×52mm
Weight	932.3g
Networking Interfaces	(4) 10/100/1000 Mbps PoE Ports (2) 1 Gbps SFP Ethernet Ports
Management Interface	Plug & Play
Switching Capacity	12Gbps
Forwarding Rate	8.9Mpps
MAC Address Table	1K, Automatic study, automatic updates
Jumbo frame	9216 Bytes
Packet buffer	1M bit
Maximum VLANs	255
Power Method	External
Input Voltage	24V-55VDC
LEDs Per Port	PWR, LNK/ACT, PoE
ESD/EMP Protection	Air: ± 8 kV, Contact: ± 6 kV
Surge Protection	Different mode ±4 kv, Common mode ±6 kv
Operating Temperature	-40°C ~ 75 °C
Operating Humidity	Air: ± 10kV, Contact: ± 8 kV
Certifications	CE, FCC, IC
PoE Interfaces	PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Max. PoE+ Wattage per Port by PSE	32W
Voltage Range 802.3at Mode	48V

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com