

5540-75

Waterproof PoE Extender



Description

60W high power PoE extender is an economic and convenient solution to help IP devices get fast network and high power supplying beyond 100 meters.

Used with 95W 5720-74 PoE injector and connecting it to your main network and power hungry IP devices can easily manage PoE distance limitation even at outdoor harsh environment with its distinguished waterproof design and simple plug and play installation.

Typical Application

Retail
Convenience Store
Workshop
Logistics
Home
and others

Specification

| Ports | |
|--------------------|---|
| Number of Ports | 1 port PoE in, 1 ports PoE out |
| Data Rate | 10/100 BaseTX |
| Transmission Media | 10BaseT Cat. 5 UTP 100BaseTX Cat. 5 UTP category5e cable |

| Electrical Characteristics | |
|-------------------------------|--|
| Standard | IEEE802.3af, IEEE802.3at |
| PoE input | 1/2(-), 3/6(+) or 7/8(-), 4/5(+) or 4 pairs working with 5720-74 |
| PoE output | 1/2(-), 3/6(+) or 7/8(-), 4/5(+) or 4 pairs working with 5720-74 |
| Max. Power Output single port | 60 W (only used with 5720-74) |
| Connectors | Shielded RJ45, EIA 568A and 568B |
| Network cables | Shielded category 5 (or higher) |
| Surge Protection | Differential mode \pm 2KV, Common mode \pm 4KV |
| MTBF | >50000 hour |
| Electrostatic standard | Contact 4KV, air 6KV |
| Weather Rating | IP67 |
| Dimensions (H x W x D) | 156.5*29*29 |
| Weight | 0.196kg |
| Operating Temperature | -10°C ~ 55°C |
| Storage Temperature | -40°C ~ 70°C |
| Humidity | 5 to 90% RH (non-condensing) |

| Standards and Regulatory | |
|--------------------------|--|
| Standards | IEEE-802.3at PoE+ / PSE IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3x Flow Control |
| Regulatory | CE, FCC Class A |

| Ordering Information | |
|-------------------------|---------|
| Waterproof PoE Extender | 5540-75 |