

5837-26

Hardened Mini Ethernet Media Converter



Description

The Fastcabling's Ethernet Media Converter is designed for application with demanding for long distance network connection. The hardened IP30 rate is suitable for outdoor harsh environment deployment. With extremely compact size, the media converter can fit for installation in limited space. It is a fair solution to gain better network access in fast speed and low latency.

Typical Application

- Retail
- Convenience Store
- Workshop
- Logistics
- Home
- and others

5837-26	
Dimensions	117x34x25mm
Weight	81g
Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX IEEE802.3x Flow Control
Networking Interfaces	(1) 100Mbps RJ45 Ethernet Ports (1) 100Mbps SFP Ethernet Ports
Management Interface	Plug & play
Forwarding Rate	100Mbps
MAC Address Table	2048K, Automatic study, automatic updates
Jumbo frame	9K Bytes
Packet buffer	1M bit
Power Method	External Terminal Block
Power Supply	DC12V
LEDs Per Port	PWR, LNK/ACT, SFP LINK
ESD/EMP Protection	Air: ± 8 kV, Contact: ± 6 kV
Surge Protection	Different mode ±4 kv, Common mode ±6 kv
Operating Temperature	-40°C ~ 75 °C
Operating Humidity	5% ~ 90% non-condensing
Certifications	CE, FCC, IC
Casing	Aluminum case
Mouting Options	Wall-mount / MR-C10 1U Raack