

# 6469-87

## Mini 5MP IR IP Camera with 2.8mm Lens



Mini 5MP IR IP Camera with 2.8mm Lens is practical tool to help small to medium size business to enhance indoor video surveillance with full HD image.

Setting up this camera easily and conveniently to monitor or safeguard property and catch more details with clear image. What's more, extremely compact size and intelligent person detection provide greater security for indoor surveillance needs.

### Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

## Specification

Camera Day/Night	
Imager	1/2.8 Type SONY Exmor CMOS Sensor
Effective Picture Elements	Effective: Approximately 5 megapixels Delivered: Approximately 5 megapixels
Lens	2.8mm
Sensitivity	IR OFF :0.001Lux IR ON :0Lux
Focus	Automatic with manual override
Iris	Automaticx1
Digital Noise Reduction	3DNR
WDR enhancement	On/Off
Gain Control	Auto/Manual/Max.
Synchronization	internal crystal
Digital Zoom	N/A
Signal-to-Noise Ratio (SNR)	>50 dB
White Balance	Auto/On/Off
Night vision	
Distance	10 m
LED	High efficiency array, 850 nm
Electrical	
Input Voltage	PoE or DC12V
Power Consumption, typical	8.0W
Software Control	
Camera Setup	Via Internet Explorer Web browser version 7.0 or later, Golbong Operation software
Supported Languages	Arabic, Portuguese, English, French, Deutscher, Russian, HUNGARIAN, ITALIAN, Japanese, POLAND, Roman, Chinese, Spanish, Turkish, SUOMI
Software Update	Firmware upload

Network	
Standards	H.265/H.264
Streaming	Two (2) independent streams: Main streams & Sub Stream
Data Rate	512 kbps to 8 Mbps
Overall IP Delay	250 ms
Resolution	Resolution (Horizontal x Vertical, PAL/NTSC)
• 5mp	2592*1944@20 fps; 1920*1080@25 fps
• 4CIF/D1	704 x 576 @ 25 fps
Ethernet	10-Base T/100 Base-TX, auto-sensing, half/full duplex, RJ45
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
User Connections	
Power Camera	DC12V, 2.0A
Video and Control	RJ-45 100 Base-TX Ethernet
Environmental	
Design Rating	IP66
Operating Temp.	-35°C to 55°C
Storage Temp.	-40°C to 60°C
Dimensions	
Weight	0.3kg
Dimensions (W x L x H)	110*110*65mm
Construction Material	
Housing	Cast aluminum
Standard Color	White